

TECHNICAL DATA SHEET

Anti-050

Anti-050 is an In-can preservative providing a broad spectrum of protective from fungi,

yeast, and bacteria for wood chip, polymer, dispersions, adhesives, paints, many household, institutional and industrial formulations and other coating system.

Anti-050 is free solvents and formaldehyde.

Properties:

Appearance : Pale blue / green clear liquid.

Density (20°C) : 1.022 - 1.032 g/ml.

Odour : Mild.

Solubility : Fully soluble in water.

Shelf life : 24 months

Dosage:

The dosage of Anti-050 required for in-can preservative of wood chip, polymer dispersions, adhesives, paints and other coating system is 0.1 - 0.3% of total weight product. The level necessary to protect a formulation depends on the composition of the formulation and the intended and use conditions. All suggested dosage should be evaluated prior to commercialization for compatibility and storage stability.

Storage conditions:

Store only in the original container. Prevent release to the environment by adequate secondary containment and use of appropriatr spill control procedures.

Further Information:

Product technical information and data is based on the best information available and does not constitute or imply a warranty or patent infringement of any kind. The user is responsible for testing product suitability prior to use in production.

630 ONNUJ 54, ONNUJ, SUANLUANG, BANGKOK 10250, THAILAND

TEL: +66 2 320 5200 FAX: +66 2 320 5208 E-MAIL: info@kernik.com WEB SITE: www.kernik.com