



TECHNICAL DATA SHEET

ILI-032 WS Grey

Product description :

ILI-032 WS Grey is an Inside Paint designed for the production of tires when high degree of slip, and maximum transfer of the Tire Lube film are important.

ILI-032 WS Grey is water based and ready to use.

ILI-032 WS Grey adheres to green tire surfaces and provides excellent release and lubrication.

ILI-032 WS Grey can be washed off after curing.

Properties:

Colour	:	Grey
Density	:	1.180 g/cm ³
Shelf life	:	12 months

Application Field:

Tires, (passengers, light truck, heavy truck, earth movers)

Advantage:

1. Water based
2. Easy to apply
3. Provides excellent release and lubrication
4. Fast drying time
5. Extend bladder life
6. Excellent finish of the tires

Application:

Apply a light film by spraying or wipe the material on by sponge into the green tire.

When sponging the green tire for refreshment, please be sure not to treat the splices/overlaps of the inliner with tire paint to prevent vulcanisation problems.

As ILI-032 WS Grey is a water based tire paint, a drying time after the green tire preparation of at least 10 minutes is necessary.

Further Information:

Product technical information and data is based on the best information available and does not constitute or imply a warranty or patent infringement of any kind. The user is responsible for testing product suitability prior to use in production.